

## **BLOCKPATCH**

### **Lightweight Patching Mortar**

**BLOCKPATCH** is a premixed fast setting cement mortar that is applied to autoclaved aerated concrete block to repair broken, chipped, or gouged areas prior to application of exterior or interior plasters.

**Surface Preparation:** All bases to receive **BLOCKPATCH** must be clean, dry, and free of grease, oil, dirt, paint, and any foreign residues.

**Mixing:** Mix one 50 pound bag with approximately 2 gallons of clean water for a few minutes and be careful not to mix more than can be used within 15 minutes.

**Application:** Apply **BLOCKPATCH** to repair area and smooth trowel to bring even with aerated concrete. Cold water and material will slow set. Warm water and material will accelerate set.

**Precautions:** Ambient and surface temperatures must be higher than 40°F within 24 hours. Protect from rain until completely hard.

**Drying Time:** Initial set is in 30 minutes. Higher strengths obtained in 24 hours.

**Cleaning:** Clean tools with water. Protect glass, metal, stone, brick, and other area from contact with plaster.

**Coverage:** One 50 pound bag will cover 32 sq/ft at 1/4 inch thickness.

**Storage:** Product storage life is one year from date of manufacture.

**Technical Data:**

Compressive Strength	700 psi
Dry Density	68 lbs/cf
Wet Density	92 lbs/cf